



SUBMITTAL - 18,000BTU WALL-MOUNT

Job Name:		,	Submitted For:	Approval		
Location:			Reference	Construction		
Engineer:			Date:			
Submitted By:			Unit Tag:			
Submitted To:			Drawing No.:			
WARRANTY						
Standard 10 Years Parts & Com	pressor		and			
When combined with Moovair outdoor unit. Term	ns & Conditions Apply.			\	1/ 6	
MODELS						
Indoor	DMA18HI	W25230E8				
CAPACITY					Images for reference only	
Cooling (Nominal Btu/h)		18000	CERTIFIED ¹			
Heating (Nominal Btu/h)		18000				
LINE SET & REFRIGERANT			CERTIFI		US energy	
Liquid (in.)		1/4"	www.ahridirecto	LISTED LISTED	ENERGY STAR	
Gas (in.) 1/2"		1. When combined with certified Moovair outdoor unit.				
Connection Type		Flared	ELECTRICAL			
Refrigerant Type		R410A	Power (From ODU)	(V/Ph/Hz)	208-230/1/60	
Drain Pipe O.D. (mm)		19	Voltage Range	(V)	187-253	
DIMENSIONS & WEIGHTS			Power Input (W)			
Indoor Net (WyDyH: in)	40.28v9	9 65×12 56	Current (A)			

43.11x12.80x15.75

12.3

16.2

27.12

35.71

INCLUDED ACCESSORIES

RG10L2(D2HS)/BGEFU1 - Remote Controller

Gross Weight lbs | kg

Gross (WxDxH; in.)

Net Weight lbs | kg

2. Performance may vary depending on system design. 3. Connection of these accessories may require secondary items not listed; refer to full product literature. | Master Group is not responsible for the accuracy and validity of any changes made to this document without the written authorization of Master Group. Specifications subject to change without notice.


ELECTRICAL	L					
Power (From ODU)		(V/Ph/Hz) 20		8-230/1/60		
Voltage Range		(V)		187-253		
Power Inpu	Power Input (W)					
Current (A)	Current (A)					
FAN ²						
Indoor	Turbo	High	Med.	Low		
CFM	635	523	376	305		
dB(A)		46	42	24		
Indoor ESP						
Indoor Moi	2.16					
OPTIONAL	ACCESSORI	ES³				
173109000						
KJR-120L(R						
KJR-120N(X						
KJR-120N1(
24VINTERF						






INDOOR UNIT DRAWING









Тоя								
Tag								
Tag inches								
mm								
Tag inches								
inches								
mm								
NOTES								